

	basic	good	very good	excellent	outstanding
Ballistic protection	●	●	●	●	○
Back face deformation	●	●	●	○	○
Fragment resistance	●	●	●	○	○
Impact absorption	●	●	○	○	○
Penetration resistance	●	●	●	○	○
Mechanical resistance					



SPECIAL PROPERTIES

- low weight
- increased comfort: 4-point adjustment harness with dial-wheel and pad system
- rail system and visor with a liquid barrier
- rail system for fast attachment of gas masks and transparent mandibles
- removable neck protection as a standard
- two component paint against abrasion
- flame-retardant shell
- Tested according to EN 397 certification

TECHNICAL SPECIFICATION

Material	fiber reinforced duroplast
Coating	Two-component paint (2K-paint)
Style	Full-Cut Anti Riot Shape
Edge protection	EPDM rubber edge
Colors	black, ranger-green, midnight-blue, white
Weight*	1850 g/4.078 lbs incl. inside equipment, neck protection, rails and visor
Standard set up	CAN-1 neck protection, CAV-1 Visor, CPP-1 Pad System, CRS-2 Harness System, CRR-1 Rail System
Size	Unisize 52-62 cm / 6½ to 8 in
Interfaces	CRR-1 rail system

*Helmet weight has natural tolerances of ±50 g - 1.7 ounces.



NORMS/CERTIFICATIONS

- shock absorption according to **EN 397, 5.1.1**
- resistance to penetration according to **EN 397, 5.1.2**
- flame-retardant according to **EN 397, 5.1.3**
- **EN 397** blunt impact resistance and resistance to penetration have been performed at -10°C/14°F (6.2.3), water immersion +20°C/68°F (6.2.5) and +50°C/122°F (6.2.4)

ACCESSORIES

- CAV-1 visor in different thickness, with AntiFog and AntiScratch coating
- helmet bag
- laser protection
- PinLock or DualLock
- mandible
- tactical identification mark

